

# Selection table

Range	Load capacity [t]	Hook path [m]	Lifting speed [m/min]			Group of mechanisms [FEM/ISO]	Range	Load capacity [t]	Hook path [m]	Lifting speed [m/min]			Group of mechanisms [FEM/ISO]				
			2-stage	Stepless	ProHub*					2-stage	Stepless	ProHub*					
														2/1	4/1	4/2	4/1
DMR 3	2/1						DMR 20	2/1									
	1	12 20 30	1.4/8	0.32-6.4	9.6	4m/M7		6.3	20 30 40 54	1.4/8	0.32-6.4 0.64-12.5 0.8-16	9.6 19 24	4m/M7				
	1.25		2/12	0.64-12.5	19	3m/M6		8		2.6/16			3m/M6				
	1.6		2.6/16	1-25	38	2m/M5		10		1/6 1.4/8 2/12			2m/M5				
	2	6 10 15	1.4/8	0.32-6.4	9.6	1Am/M4		12.5	7.6 14.6 21.6 31.3	1.4/8	0.32-6.4 0.64-12.5 0.8-16	9.6 19 24	1Am/M4				
	4/1							4/2									
	2		0.7/4	0.16-3.2	4.8	4m/M7		6.3		1.4/8			4m/M7				
	2.5		1/6	0.32-6.4	9.6	3m/M6		8		2/12			3m/M6				
	3.2	1.3/8	0.5-12.5	19	2m/M5	10		2.6/16	2m/M5								
	4	0.7/4	0.16-3.2	4.8	1Am/M4	12.5		1/6 1.4/8	1Am/M4								
DMR 5	2/1						DMR 20	4/1									
	1.6	12 20 30	1.4/8	0.32-6.4	9.6	4m/M7		12.5	10 15 20 27	0.7/4	0.16-3.2 0.32-6.4 0.4-8	4.8 9.6 12	4m/M7				
	2		2/12	0.64-12.5	19	3m/M6		16		1/6 1.3/8			3m/M6				
	2.5		2.6/16	1-25	38	2m/M5		20		0.5/3 0.7/4 1/6			2m/M5				
	3.2	9.9 16.3	1.4/8	0.32-6.4	9.6	1Am/M4		25	7.8 11.3 16.1 27.1	1.4/8	0.32-6.4 0.4-8	9.6 12	1Am/M4				
	4/2							8/2									
	3.2		0.7/4	0.16-3.2	4.8	4m/M7		12.5		0.7/4			4m/M7				
	4		1/6	0.32-6.4	9.6	3m/M6		16		1/6			3m/M6				
	5	1.3/8	0.5-12.5	19	2m/M5	20		1.3/8	2m/M5								
	6.3	0.7/4	0.16-3.2	4.8	1Am/M4	25		0.5/3 0.7/4 1/6	1Am/M4								
DMR 10	2/1						DMR 20	6/1									
	3.2	12 20 30 40	1.4/8	0.32-6.4	9.6	4m/M7		20	6.7 10 13.3 18	0.7/4	0.22-4.3 0.26-5.3	6.4 8	4m/M7				
	4		2/12	0.64-12.5	19	3m/M6		25		0.9/5.3			3m/M6				
	5		2.6/16	1-25	38	2m/M5		32		0.7/4			2m/M5				
	6.3	5.8 11.35 18.4 25.2	1.4/8	0.32-6.4	9.6	1Am/M4		40	8 11.2 18	0.7/4	0.22-4.3 0.26-5.3	6.4 8	1Am/M4				
	4/2							12/2									
	3.2		0.7/4	0.16-3.2	4.8	4m/M7		20		0.7/4			4m/M7				
	4		1/6	0.32-6.4	9.6	3m/M6		25		0.9/5.3			3m/M6				
	5	1.3/8	0.5-12.5	19	2m/M5	32		0.7/4	2m/M5								
	6.3	0.7/4	0.16-3.2	4.8	1Am/M4	40		0.7/4	1Am/M4								
DMR 16	4/1						DMR 20	8/1									
	6.3	6 10 15 20	0.7/4	0.16-3.2	4.8	4m/M7		25	7.5 10 13.5 21.3	0.5/3	0.16-3.2 0.2-4	4.8 6	4m/M7				
	8		1/6	0.32-6.4	9.6	3m/M6		32		0.7/4			3m/M6				
	10		1.3/8	0.5-12.5	19	2m/M5		40		0.5/3			2m/M5				
	12.5	0.7/4	0.16-3.2	4.8	1Am/M4	50		0.5/3	1Am/M4								
	6/1							6/1									
	12.5	6.7 13.3	0.7/4	0.22-4.3	6.4	3m/M6		12.5	6.7 13.3	0.9/5.3	0.32-8.3	12.6	3m/M6				
	16		0.9/5.3	0.32-8.3	12.6	2m/M5		16		0.9/5.3			2m/M5				

\* ProHub: 50 % higher lifting speed for up to 30 % of rated load capacity.