

Request For Quote | DVR Crane Packages



Company: _____

Name: _____

Phone: _____

E-mail: _____

General

Type of crane: Single girder Double girder

End trucks: Top running Under running

Type of hoist: Wire Rope Chain

Capacity: _____

Lift: _____

Span: _____

Voltage: 460-3-60Hz 230-3-60Hz 208-3-60Hz 575-3-60Hz Other: _____

Control: DSB pendant (standard) DSX pendant (optional) Radio

Electrification: C-track festoon NRGmaster

Hoist, Trolley & Bridge

Hoist speed: _____

Hoist control: Two-speed (standard)
 Variable speed → Open loop **OR** Closed loop

Reeving: Single-reeved Double-reeved

Trolley speed: _____ Two-speed Variable speed (standard) Anti-sway

Bridge speed: _____ Two-speed Variable speed (standard) Anti-sway

Runway rail size (top running)/ Runway beam flange (under running): _____

Environment and Duty Cycle

Location of use: Indoor Outdoor Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): _____

Hoist duty cycle (ASME/FEM): H3/1Am H4/2m H4+/3m

Trolley duty cycle (CMAA/FEM): Class C/2m Class D/3m

Bridge duty cycle (CMAA/FEM): Class C/2m Class D/3m

Quote Required By: _____

Notes: