

REQUEST FOR QUOTE - DVR ROPE HOISTS **DEMAG**

Company: _____

Name: _____

Phone: _____

E-mail: _____

General

Capacity: _____

Lift: _____

Suspension:

☐ Lugmount

☐ Footmount

☐ Push trolley

☐ Normal headroom

☐ Low headroom

☐ Double girder

Voltage: ☐ 460-3-60Hz ☐ 230-3-60Hz ☐ 208-3-60Hz ☐ 575-3-60Hz ☐ Other: _____

Hoist And Trolley

Hoist speed: _____

Hoist control:

☐ Two-speed (standard)

☐ Variable speed



☐ Open loop

OR ☐ Closed loop

Reeving:

☐ Single-reeved

☐ Double-reeved

Trolley speed: _____

Trolley control:
(standard)

☐ Two-speed

☐ Variable speed

For double girder, specify: trolley gauge AND trolley rail size: _____

For single girder, specify: beam type OR flange width: _____

Controls

☐ SOLO CONTROLS (We'll add a mainline contactor and control transformer.)

☐ CRANE CONTROLS (The mainline and control transformer are assumed to be supplied by others.)

For Monorail → ☐ Straight track ☐ Curved track : Radius _____

Pendant required? ☐ No ☐ Yes Specify Motions: _____ Length: _____

Environment And Duty Cycle

Location of use: ☐ Indoor ☐ Outdoor ☐ Outdoor Under Roof

Ambient temperature (Standard is 14-104° F / -10-40° C): _____

Hoist duty cycle (ASME/FEM):

☐ H3/1Am

☐ H4/2m

☐ H4+/3m

Trolley duty cycle (CMAA/FEM):

☐ Class C/2m

☐ Class D/3m

QUOTE REQUIRED BY: _____

NOTES: