

Request For Quote | Crane Packages



Company: _____

Name: _____

Phone: _____

E-mail: _____

General

Type of crane: ☐ Single girder ☐ Double girder

End trucks: ☐ Top running ☐ Under running

Type of hoist: ☐ Wire Rope ☐ Chain

Capacity: _____

Lift: _____

Span: _____

Voltage: ☐ 460-3-60Hz ☐ 230-3-60Hz ☐ 208-3-60Hz ☐ 575-3-60Hz ☐ Other: _____

Control: ☐ DSB pendant (standard) ☐ DSX pendant (optional) ☐ Radio

Electrification: ☐ C-track festoon ☐ NRGmaster

Hoist, Trolley & Bridge

Hoist speed: _____

Hoist control: ☐ Two-speed (standard)
☐ Variable speed → ☐ Open loop **OR** ☐ Closed loop

Reeving: ☐ Single-reeved ☐ Double-reeved

Trolley speed: _____ ☐ Two-speed ☐ Variable speed (standard) ☐ Anti-sway

Bridge speed: _____ ☐ Two-speed ☐ Variable speed (standard) ☐ Anti-sway

Runway rail size (top running)/ Runway beam flange (under running): _____

Environment and Duty Cycle

Location of use: ☐ Indoor ☐ Outdoor ☐ Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): _____

Hoist duty cycle (ASME/FEM): ☐ H3/1Am ☐ H4/2m ☐ H4+/3m

Trolley duty cycle (CMAA/FEM): ☐ Class C/2m ☐ Class D/3m

Bridge duty cycle (CMAA/FEM): ☐ Class C/2m ☐ Class D/3m

Quote Required By: _____

Notes: