

Request For Quote | KBK Monorail



Company: _____

Name: _____

Phone: _____

E-mail: _____

Monorail

Support Method: Free-standing Portal Structure Free-standing Lampost Structure
 Ceiling Mounted Structure Support steel flange width _____

Profile Width / Beam Type: _____ Steel Aluminum

Capacity: _____ Monorail Length: _____ Distance between support centers: _____

Clearance Height: _____ Concrete Type & Concrete Thickness: _____

]Electric Supply: Electric Festoon Internal Busbar
 Air Clean (balancer) *OR* Lubricated (air hoist)
 None Festoon Hose *OR* Coiled Hose

Voltage: 460-3-60Hz 230-3-60Hz 208-3-60Hz 575-3-60Hz Other: _____

OR Air Pressure (PSI): _____

Location of use: Indoor Outdoor Outdoor under roof Corrosive Environment
Environment notes: _____

Hoist & Trolley

Capacity: _____ Lifting Height: _____

Hoist type: Two-speed (standard) Variable speed Electric Balancer Air Balancer Air Hoist
Hoisting Speed: 32 FPM (standard) Non-standard speed (specify) _____
Reeving: Single-reeved Double-reeved

Trolley: Manual Tractor Drive Two-speed **OR** Variable speed (standard)

Other lifting devices or notes (specify): _____

Quote Required By: _____

Notes: