

# Selection table

Range	SWL	Hook path	Lifting speed			Group of mechanisms	SWL	Hook path	Lifting speed		
	t		m	m/min			t		m	m/min	
DR 3	2/1						4/1				
	1.6	12 20	12/2	18/3	1-25 *	2m / M5 **	3.2	6 10	6/1	9/1.5	0.5-12.5 *
	1.25					3m / M6 **	2.5				
	1					4m / M7 **	2				
DR 5	2/1						4/1				
	3.2	12 20 30	9/1.5	12/2	0.8-16 *	1Am / M4 **	6.3	6 10 15	4.5/0.8	6/1	0.4-8 *
	2.5		12/2	18/3	1-25 *	2m / M5 **	5		6/1	9/1.5	0.5-12.5 *
	2					3m / M6 **	4				
	1.6					4m / M7 **	3.2				
	4/2										
	3.2	9.9 16.3	9/1.5	12/2	0.8-16 *	1Am / M4 **					
	2.5		12/2	18/3	1-25 *	2m / M5 **					
	2					3m / M6 **					
	1.6					4m / M7 **					
DR 10	2/1						4/1				
	6.3	12 20 30 40	8/1.4	0.4-9 *	1-18 *	1Am / M4 **	12.5	6 10 15 20	4/0.7	0.2-4.5 *	0.5-9 *
	5		10/1.7	1-18 *	1-25 *	2m / M5 **	10		5/0.8	0.5-9 *	0.5-12.5 *
	4					3m / M6 **	8				
	3.2					4m / M7 **	6.3				
	4/2						6/1				
	6.3	5.8 11.35 18.4 25.2	8/1.4	0.4-9 *	1-18 *	1Am / M4 **		6.7 13.3	2.7/0.4	0.3-6 *	-
	5		10/1.7	1-18 *	1-25 *	2m / M5 **	16				
	4					3m / M6 **	12.5				
	3.2					4m / M7 **					
DR 20	2/1						4/1				
	12.5	24 36 54	6/1	12/2	1-16 *	1Am / M4	25	12 18 27	3/0.5 6/1	0.5-5 *	0.5-8 *
	10					2m / M5	20				
	8					3m / M6	16				
	6.3					4m / M7	12.5				
	4/2						6/1				
	12.5	12.3 21.2 33.2	6/1	12/2	1-16 *	1Am / M4	40	12 18 24.7	4/0.7	0.3-3.3 *	0.3-5.3 *
	10					2m / M5	32				
	8					3m / M6	25				
	6.3					4m / M7	20				
	8/2						8/1				
	25	10.3 16.3 23.4	3/0.5 6/1	0.5-5 *	0.5-8 *	1Am / M4	50	9 13.5 18.5	3/0.5	0.3-2.5 *	0.2-4 *
	20					2m / M5	40				
	16					3m / M6	32				
12.5	4m / M7					25					

\* Loads weighing up to one third of the rated load are moved at 1.5 times the rated speed (Prohub)

\*\* Gearbox service life 20 % longer than the ISO/FEM full load service life